



# Oa2ki®

POWDER

## DESICCANT POWDER DIATOMACEOUS EARTH

PRODUCED FROM  
**FOSSILISED DIATOMS**

**4 kg e**

Oa2ki® powder is produced from fossilised diatoms.  
The powder is able to desiccate any area where it is applied.

#### Application instructions

Oa2ki® can be applied directly as dust or as a slurry to the areas where desiccated application is required.

Apply as required directly on the area, up to 10-30 g/m<sup>2</sup> of hard surface.  
Application can be repeated after 15 days.

When applied as a slurry, the recommended dilution rate is 1 part Oa2ki® to 2.5 litres of water. This solution can be painted and left to dry. Stir on a regular basis during application.

When applying Oa2ki® it is recommended to use appropriate personal protective equipment (gloves, coveralls and mask FFP2 EN149 or DIN 58 646- HM fitted with a P2 filter DIN EN 143 and only re-enter the area when dust has settled.

**DO NOT BREATHE POWDER. KEEP OUT OF THE REACH OF CHILDREN. DUST PARTICLES IN EYES CAN BE WASHED OUT WITH CLEAN WATER.**

St. Ivel Way, Warmley, Bristol BS30 8TY.  
T: 0117 967 2222 F: 0117 961 4122  
E: [beh@barrettine.co.uk](mailto:beh@barrettine.co.uk)  
[www.barrettine.co.uk](http://www.barrettine.co.uk)

**Barrettine**  
Environmental Health